

میکسر آزمایشگاهی Bascet Mill

میکسر آزمایشگاهی: میکسر آزمایشگاهی LSM عمدتاً برای مواد خمیری مایع مختلف مانند رنگ، جوهر چاپ، رنگدانه و غیره استفاده می شود (برای موادی با ترکیبات اسید-باز یا رنگ که منجر به خوردگی ماشین می شود مناسب نیست) این دستگاه از موتور DC تشکیل شده است و کنترل دور با صفحه نمایش دیجیتال انجام می گردد. سبک و ظریف نمونه دارای خط داخلی برای خنک کننده هستند. این طراحی برای کاهش دمای آسیاب تعبیه شده است و از گرم شدن بیش از حد جلوگیری می کند.



مشخصات فنی میکسر Bascet Mill

Model	LSM-2.2D	LSM-2.2B	LSM-370	LSM-750A
Motor Type	Brushless DC	AC Explosion proof	Brushless DC	AC variable frequency
Power	2.2KW	2.2KW	550W	750W
Speed Range	50~4000rpm	0~4000rpm	50~4000rpm	0~4000rpm

Lifting Distance	350mm	400mm	240mm	200mm
Zirconia Bead	Φ1.4~Φ1.6mm	Φ1.4~Φ1.6mm	Φ1.4~Φ1.6mm	Φ1.8~Φ2.0mm
Milling Impellers	Φ107mm	Φ90mm	Φ44mm	Φ68mm
Dispersion Impellers	Φ120mm	Φ120mm	Φ60mm	Φ60mm
Container	10~30L	20L	1.25L	2.9L
Overall Size	580×500×850mm	600×550×850mm	450×420×550mm	400×340×650mm
Packing size	650×570×1010mm	650×570×1010mm	580×540×610mm	580×540×610mm
Electrical Source	220V 50/60Hz	380V 50/60Hz	220V 50/60Hz	220V 50/60Hz
Weight	60kg	96kg	22kg	29kg
Gross weight	87	132	28.9+4.1 (charging barrel)	35.9+7.3 (charging barrel)



Configuration list :

Type	LSM-2.2B	LSM-2.2D	LSM-370	LSM-750A
Machine	1	1	1	1
F120 Dispersion disc (mounted on the shaft)	1	1	/	/
Zirconium bead	1	1	1	1
Copper-based oilless bearing1410	5	5	5	5
Explosion-proof button box	1	/	/	/
electric cabinet (Non-explosion-proof)	1	/	/	/
Instructions	1	1	1	1
Certificate	1	1	1	1



Ordering Information:

Type	Name
LSM-2.2D	Electric Lift Basket Mill
LSM-2.2B	Explosion-proof Basket Mill
LSM-370	Lab Basket Mill
LSM-750A	Lab Basket Mill
Accessories	Full explosion-proof control box
Accessories	Semi-explosion-proof control box