

## پی اچ متر پرتابل HI8314



### مشخصات پی اچ متر پرتابل HI8314

- دارای الکتروود pH از پیش تقویت شده
- دارای کالیبراسیون دستی یک یا دو نقطه ای آسان
- دارای جبران خودکار دما
- دارای نشانگر کم بودن باتری
- HI8314 بک دستگاه پرتابل اندازه گیری پی اچ / mV / دما طراحی شده است تا قابل اطمینان و دارای استفاده آسان باشد.
- HI8314 از الکتروود pH و سنسور دمای داخلی HI1217D استفاده می کند.

### کالیبراسیون دستی در یک یا دو نقطه

این دستگاه برای کاربردهایی که به یک نقطه کالیبراسیون سفارشی نیاز دارند ایده آل است. برای دستیابی به دقت بهتر ، کالیبراسیون دستی می تواند بسیار مفید باشد.



لطفاً جهت خرید HI8314 HANNA و یا آگاهی از قیمت روز پی اچ متر پرتابل [HI8314](#) با ما تماس بگیرید.

مشخصات فنی پی اچ متر پرتابل: HI8314

Range	pH	0.00 to 14.00 pH
	ORP	±1999 mV
	Temperature	0.0 to 100.0°C
Resolution	pH	0.01 pH
	ORP	1 mV
	Temperature	0.1°C
Accuracy	pH	±0.01 pH
	ORP	±1 mV
	Temperature	±0.4°C (excluding probe error)
pH Calibration		manual, two point, through trimmers (offset ±1 pH; slope: 80 to 110%)
Temperature Compensation		Automatic, 0 to 70°C (32 to 158°F)
Probe		HI1217D PEI body, pre-amplified pH electrode with internal temperature sensor, DIN connector and 1 m cable (included)
Input Impedance		10 <sup>12</sup> Ohm
Battery Type / Life		9V / approximately 100 hours of continuous use
Environment		0 to 50°C (32 to 122°F); RH max 100%
Dimensions		145 x 80 x 36 mm (5.7 x 3.1 x 1.4")
Weight		230 g (8.1 oz.)