

سختی سنج پرتابل هانا مدل HI8734

دستگاه TDS HI8734 با چند دامنه ۰,۰ تا ۱۹,۹۹ گرم در لیتر (ppt).



HI8734 دستگاهی پرتابل است که TDS کل مواد جامد محلول) را در بیش از ۳ دامنه اندازه گیری می کند. دستگاه دارای یک پراب ۴ حلقه ای قوی است و قرائت سریع و دقیق را تضمین می کند. جبران دما با کمک سنسور دما در پراب بصورت خودکار انجام می شود HI8734. همه کاره است.



مشخصات کلی سختی سنج پرتابل هانا مدل HI8734

- نمایشگر بزرگ پشتیبانی کاربر
- محدوده چند اندازه گیری
- اندازه گیری انتخاب دامنه با فشار دادن ساده یک دکمه
- الکتروود ۴ حلقه
- دستکاری آسان
- اطلاعات پشتیبانی کاربر در هنگام کالیبراسیون
- نشانگر شارژ باتری

لطفا جهت خرید، قیمت و مشخصات فنی سختی سنج پرتابل [هانا](#) مدل HI8734 ، با ما تماس بگیرید.

مشخصات فنی سختی سنج پرتابل هانا مدل HI8734

Measuring range	0.0 to 199.9 mg / L (ppm); 0 to 1999 mg / L (ppm); 0.00 to 19.99 g / L (ppt)
resolution	0.1 mg / L (ppm); 1 mg / L (ppm); 0.01 g / L (ppt)
accuracy	± 2% of the display (probe errors excluded)
calibration	Manual, 1 point
Correction of temperature	Manual, 0 to 50 ° C with $\beta = 2\% / ^\circ \text{C}$
probe	HI 76301D (included)
Power supply	1 x 9 V battery / approx. 100 operating hours
Dimensions	145 x 80 x 36 mm
Weight	230 g